

NATURAL GAS FIRED CHP PB 250SNG

SPECIFICATION DATASHEET

Operation:	Mains parallel Synchronous
Fuel:	Natural gas
Electrical power modulation:	125-252 kW(e)
Thermal output:	289 kW(t)
Electrical efficiency:	39.2%
Flow temperature max:	90 ° C
Return temperature max:	76 ° C
Exhaust temperature:	120 ° -150 ° C
Exhaust gas flow:	1918 m ³ /hr (Max)
Exhaust emission at:	CO <1000 mg/Nm ³ NO _x <700mg/m ³ @ 0% O ₂
Efficiency:	87.6%
Voltage:	400 V
Power Factor:	cos phi 0.98
Sound Power Level:	<65 dBA (at 1 metre)
Fuel Consumption:	680 kW



image for illustration purposes only

Engine

Model:	MAN
Type:	E2848LE22

Alternator

Voltage:	400 V
Width:	50 Hz
Height:	1550 rpm

Heat Exchanger Module Dimensions

Length:	3390 mm
Width:	1000 mm
Height:	2880 mm

CHP Dimensions & Connections

Length	3200 mm
Width	1400 mm
Height	1810 mm
Weight	3500 kg
Heating flow	R 3 inch
Heating return	R 3 inch
Exhaust port	R 4 inch
Gas connection	R 2 inch

NATURAL GAS FIRED CHP PB 250SNG

PRIME MOVER UNIT

CONSTRUCTION

- Rigid base frame made of powder coated square section steel tube and profiled steel sections.
- Independent engine and alternator assemblies close coupled with Cush Drive, mounted on four bonded rubber mountings
- Complete hydraulic separation of engine coolant system from building heating system via stainless steel plate heat exchanger
- All electrical components are prewired to central connection point
- Frame is further isolated by four anti vibration mounting feet, for the best prevention of structure borne sound transmission.

CASING

- Highly effective sound absorbing enclosure constructed from:
 - Powder coated steel plate
 - Sound deadening material
 - Rockwall thermal insulation
 - Perforated galvanized steel inner skin
 - Removable side panels allow swift access to all components.

HYDRAULIC SYSTEM REQUIREMENTS

- System Kit does not include:
 - Customer circuit water pump.
 - Customer circuit expansion vessel
 - Customer circuit pressure relief valve
 - Customer plate heat exchange interface

EXHAUST SYSTEM

- Water-cooled exhaust manifold, maintenance-free stainless steel heat exchangers and exhaust silencing in unit enclosure.

GAS

- Gas control from DVGW tested assemblies consisting
 - Gas block with integrated multi-gas filter,
 - Pressure regulator;
 - Gas-air mixer with throttle.

CONTROL

- Electronic Speed Control
- Speed sensor and actuator for precise frequency and power control.
- Woodward Easygen controller

CONTROL CABINET

CONSTRUCTION

- Mounted on CH, made of sheet steel 1.5 mm,

FEATURES

- Automatic start/stop
- Full system monitoring
- Fault monitoring and fault indication in plain text
- Automatic Power control and modulation
- Lambda control optional
- Timer function to optimise the operating hours

MOTOR / GENERATOR PROTECTION

- Overload monitoring
- Reverse power monitoring
- Inlet temperature monitoring
- Flow temperature control
- Oil pressure
- Motor temperature monitoring
- Exhaust temperature monitoring
- Gas Monitoring
- Leakage monitoring
- Generator Temperature Monitoring

METERING

- Electric meters (kWh)
- Hour meter
- Start counter

RECORDING

- Logbook history
- Fault memory

CONTROL

- Main switch with Emergency Stop Function
- Easy access keypad on control panel
- Full remote access and control via modem or broadband
- Fault notification via email
- Interface to BMS via Ethernet UDP, Mod-bus RTU, RK512, 3964R
- Ability to control back up boilers

CONTROL OUTPUTS

- Gas valve signal
- External fault signal

CONTROL INPUTS

- External run request
- Boiler room emergency switch signal
- External power requirement

NETWORK PROTECTION FUNCTIONS

- G59 Relay, monitoring voltage, frequency and rate of change of frequency (RoCoF)

PROTECTION

- Short-circuit protection
- G59 Electrical Protection Relay
- Performance Monitoring of CHP system
- Current monitoring of CHP and Electrical Network

SWITCHING TO THE GRID

- Unit has independent starter motor
- Black Start and Island Mode options available

According to our business policy and the continuing development of our products, we reserve the right to change specifications and features without notice.



For information in England and Wales contact Helec Ltd



www.helec.co.uk

Helec Ltd
Lye Cross Road, Redhill,
Bristol, BS40 5RH
T: 01934 862264
F: 01934 863582
E: info@helec.co.uk

For information in North England and Scotland contact Hevac Ltd



www.hevac.ltd.uk

Unit A, 1 Young Place,
Kelvin Industrial Estate
East Kilbride G75 0TD
T: 01355 248664
F: 01355 242746
E: dmac@hevac.ltd.uk