

## NATURAL GAS FIRED CHP PB 250SNG

### SPECIFICATION DATASHEET

Operation:	Mains parallel Synchronous
Fuel:	Natural gas
Electrical power output:	240 kW/e (min<148 kW/e)
Thermal output:	280 kW/t (min<178 kW/t)
Electrical efficiency:	39.2%
Flow temperature max:	90 ° C
Return temperature max:	76 ° C
Exhaust temperature:	120 ° -150 ° C
Exhaust gas flow:	1918 m <sup>3</sup> /hr (Max)
Exhaust emission at:	CO <1000 mg/Nm <sup>3</sup> NOx <700mg/m <sup>3</sup> @ 0% O <sub>2</sub>
Efficiency:	87.6%
Voltage:	400 V
Power Factor:	cos phi 0.98
Sound Power Level:	<65 dBA (at 1 metre)
Fuel Consumption:	680 kW



*image for illustration purposes only*

#### Engine

Model:	L6 Liebherr
Type:	G946

#### Alternator

Voltage:	400 V
Freequency:	50 Hz
Rated speed:	1550 rpm

#### CHP Dimensions & Connections

Length	3200	mm
Width	1400	mm
Height	1810	mm
Weight	3500	kg
Heating flow	R 3	inch
Heating return	R 3	inch
Exhaust port	R 4	inch
Gas connection	R 2	inch

# NATURAL GAS FIRED CHP PB 250SNG

## PRIME MOVER UNIT

### CONSTRUCTION

- Rigid base frame made of powder coated square section steel tube and profiled steel sections.
- Independent engine and alternator assemblies close coupled with Cush Drive, mounted on four bonded rubber mountings
- Complete hydraulic separation of engine coolant system from building heating system via stainless steel plate heat exchanger
- All electrical components are prewired to central connection point
- Frame is further isolated by four anti vibration mounting feet, for the best prevention of structure borne sound transmission.

### CASING

- Highly effective sound absorbing enclosure constructed from:
  - Powder coated steel plate
  - Sound deadening material
  - Rockwall thermal insulation
  - Perforated galvanized steel inner skin
  - Removable side panels allow swift access to all components.

### HYDRAULIC SYSTEM REQUIREMENTS

- System Kit does not include:
  - Customer circuit water pump.
  - Customer circuit expansion vessel
  - Customer circuit pressure relief valve
  - Customer plate heat exchange interface

### EXHAUST SYSTEM

- Water-cooled exhaust manifold, maintenance-free stainless steel heat exchangers and exhaust silencing in unit enclosure.

### GAS

- Gas control from DVGW tested assemblies consisting
  - Gas block with integrated multi-gas filter,
  - Pressure regulator,
  - Gas-air mixer with throttle.

### CONTROL

- Electronic Speed Control
- Speed sensor and actuator for precise frequency and power control.
- Woodward Easygen controller

## CONTROL CABINET

### CONSTRUCTION

- Mounted on CH, made of sheet steel 1.5 mm,

### FEATURES

- Automatic start/stop
- Full system monitoring
- Fault monitoring and fault indication in plain text
- Automatic Power control and modulation
- Lambda control optional
- Timer function to optimise the operating hours
- 5.7" LCD display panel
- Panel mounted keyboard access

### MOTOR / GENERATOR PROTECTION

- Overload monitoring
- Reverse power monitoring
- Inlet temperature monitoring
- Flow temperature control
- Oil pressure
- Motor temperature monitoring
- Exhaust temperature monitoring
- Gas Monitoring
- Leakage monitoring
- Generator Temperature Monitoring

### METERING

- Electric meters (kWh)
- Hour meter
- Start counter

### RECORDING

- Logbook history
- Fault memory

### CONTROL

- Main switch with Emergency Stop Function
- Easy access keypad on control panel
- Full remote access and control via modem or broadband
- Fault notification via email
- Interface to BMS via Ethernet UDP, Mod-bus RTU, RK512, 3964R
- Ability to control back up boilers

### CONTROL OUTPUTS

- Gas valve signal
- External fault signal

### CONTROL INPUTS

- External run request
- Boiler room emergency switch signal
- External power requirement

### NETWORK PROTECTION FUNCTIONS

- G59 Relay, monitoring voltage, frequency and rate of change of frequency (RoCoF)

### PROTECTION

- Short-circuit protection
- G59 Electrical Protection Relay
- Performance Monitoring of CHP system
- Current monitoring of CHP and Electrical Network

### SWITCHING TO THE GRID

- Unit has independent starter motor
- Black Start and Island Mode options available

*According to our business policy and the continuing development of our products, we reserve the right to change specifications and features without notice.*



For information in England and Wales contact Helec Ltd



[www.helec.co.uk](http://www.helec.co.uk)

Helec Ltd  
Lye Cross Road, Redhill,  
Bristol, BS40 5RH  
T: 01934 862264  
F: 01934 863582  
E: [info@helec.co.uk](mailto:info@helec.co.uk)

For information in North England and Scotland contact Hevac Ltd



[www.hevac.ltd.uk](http://www.hevac.ltd.uk)

Unit A, 1 Young Place,  
Kelvin Industrial Estate  
East Kilbride G75 0TD  
T: 01355 248664  
F: 01355 242746  
E: [edmac@hevac.ltd.uk](mailto:edmac@hevac.ltd.uk)